

## Cam follower CR22-VR-IKO - CR22-VR-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr22-vr-iko>

**IKO**  
**CAM FOLLOWERS**  
Inch Series Cam Followers Full Complement Type/With Screwdriver Slot

Stud dia. mm (inchi)	Identification number				Mass (Ref.)					
	Shield type		Shield type		$\phi$	$D$	$C$	$d_1$	$G$	$G_1$
	With cover	With cylindrical outer ring	With shielded outer ring	With cylindrical outer ring					UNF	
12.700 ( $\frac{1}{2}$ )	CR 22	VR			160	34.925 ( $1\frac{3}{8}$ )	19.050 ( $\frac{3}{4}$ )	12.700 ( $\frac{1}{2}$ )	-20	15.875 ( $\frac{5}{8}$ )

  

Boundary dimensions mm(inch)							Mounting dimension $f$ Min. mm(inch)	Maximum tightening torque $C$ N·m	Basic dynamic load rating $C_0$ N	Basic static load rating $C_0$ N
$B_{max}$	$B_2$	$B_3$	$C_1$	$g_1$	$g_2$	$r$				
28.4 (1.12)	21.750 ( $\frac{7}{8}$ )	7.938 ( $\frac{5}{16}$ )	0.794 ( $\frac{1}{16}$ )	4.762 ( $\frac{3}{16}$ )	3.175 ( $\frac{1}{8}$ )	1.588 ( $\frac{1}{16}$ )	21.628 ( $\frac{7}{8}$ )	27.7	22 800	31 700

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463784
Inside diameter	12.7 mm
Outside diameter	34.925 mm
Thickness	19.05 mm
Weight	160 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE