

Cam follower CR24-V-IKO - CR24-V-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr24-v-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.)					
	Shield type		Splayed type		g	D	C	d ₁	G	G ₁
	With covered outer ring	With cylindrical outer ring	With splayed outer ring	With cylindrical outer ring						
15.875 (5/8)		CR 24 V			230	38.100 (1 1/2)	22.225 (7/8)	15.875 (5/8)	G 1/8	19.050 (3/4)

Boundary dimensions mm(inch)							Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
B max	B ₂	B ₃	C ₁	g ₁	g ₂	r				
22.8 (0.90)	38.100 (1 1/2)	9.525 (3/8)	0.794 (1/32)	4.762 (3/16)	3.989 (5/32)	1.588 (1/16)	26.166 (1 1/8)	55.7	28 200	40 100

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463876
Inside diameter	15.875 mm
Inside diameter	5/8" inch
Outside diameter	38.1 mm
Outside diameter	1 1/2" inch
Thickness	22.225 mm
Thickness	7/8" inch
Weight	230 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE