


Cam follower CR24-VBR-IKO - CR24-VBR-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr24-vbr-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	Shield type					
	Shield type		Shield type			a	D	C	d ₁	G UNF	G ₁
	With cover outer ring	With cylindrical outer ring	With cover outer ring	With cylindrical outer ring							
15.875 ($\frac{5}{8}$)	CR 24	VBR			230	38.100 ($\frac{1}{2}$)	22.225 ($\frac{7}{8}$)	15.875 ($\frac{5}{8}$)	$\frac{1}{4}$ -18	19.050 ($\frac{3}{4}$)	
Boundary dimensions mm (inch)											
B max	B ₂	B ₃	C ₁	g ₁	g ₂	H	r	Mounting dimension f Min. mm (inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
23.6 (0.93)	38.100 ($\frac{1}{2}$)	9.525 ($\frac{3}{8}$)	0.794 ($\frac{1}{16}$)	4.762 ($\frac{3}{16}$)	3.969 ($\frac{1}{8}$)	7.938 ($\frac{1}{2}$)	1.588 ($\frac{1}{16}$)	25.195 ($\frac{1}{2}$)	55.7	29 200	40 100

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463906
Inside diameter	15.875 mm
Outside diameter	38.1 mm
Thickness	22.225 mm
Weight	230 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE