

## Cam follower CR26-V-IKO - CR26-V-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr26-v-iko>

IKO

### CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.)					
	Shield type		Sleeved type		$\phi$	$D$	$C$	$d_1$	$G$	$G_1$
	With covered outer ring	With cylindrical outer ring	With shielded outer ring	With cylindrical outer ring					UNF	
15.875 ( $\frac{5}{8}$ )		CR 26 V			265	41.275 ( $\frac{1}{2}$ )	22.225 ( $\frac{7}{8}$ )	15.875 ( $\frac{5}{8}$ )	$\frac{1}{2}$ -18	18.050 ( $\frac{7}{8}$ )

  

Boundary dimensions mm(inch)							Mounting dimension $r$ Min. mm(inch)	Maximum tightening torque $C$ N·m	Basic dynamic load rating $C_0$ N	Basic static load rating $C_0$ N
$B$ max	$B_2$	$B_3$	$C_1$	$g_1$	$g_2$	$r$				
23.8 (0.94)	38.100 (1.5)	9.525 ( $\frac{3}{8}$ )	0.794 ( $\frac{1}{4}$ )	4.762 ( $\frac{3}{8}$ )	3.969 ( $\frac{5}{16}$ )	1.588 ( $\frac{1}{8}$ )	26.166 (1.03)	55.7	28 200	40 100

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463951
Inside diameter	15.875 mm
Inside diameter	5/8" inch
Outside diameter	41.275 mm
Outside diameter	1 5/8" inch
Thickness	22.225 mm
Thickness	7/8" inch
Weight	265 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE