


Cam follower CR26-VUU-IKO - CR26-VUU-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr26-vuu-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



CR-VUU

Stud dia. mm (inch)	Identification number				Mass (Ref.)					
	Shield type		Sleeved type		ϕ	D	C	d_1	G UNF	G_1
15.875 ($\frac{5}{8}$)	With covered outer ring	With cylindrical outer ring	With drilled outer ring	With cylindrical outer ring						
				CR 26 VUU	265	41.275 ($\frac{1}{2}$)	22.225 ($\frac{7}{8}$)	15.875 ($\frac{5}{8}$)	$\frac{1}{2}$ -18	19.050 ($\frac{3}{4}$)

Boundary dimensions mm(inch)							Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C_0 N
B max	B_2	B_3	C_1	g_1	g_2	r				
23.8 (0.94)	38.100 ($\frac{1}{2}$)	9.525 ($\frac{3}{8}$)	0.794 ($\frac{1}{16}$)	4.762 ($\frac{3}{16}$)	3.969 ($\frac{5}{32}$)	1.588 ($\frac{1}{16}$)	26.166 ($\frac{1}{2}$)	55.7	28 200	40 100

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463975
Inside diameter	15.875 mm
Outside diameter	41.275 mm
Thickness	22.225 mm
Weight	265 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE