


Cam follower CR26-VBUU-IKO - CR26-VBUU-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr26-vbuu-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



CR26-VBUU

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring							
15.875 (5/8)				CR 26 VBUU	265	41.275 (1 1/2)	22.225 (7/8)	15.875 (5/8)	1/4-18	19.050 (3/4)	
Boundary dimensions mm(inch)						Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N		
B max	B ₂	B ₃	C ₁	g ₁	g ₂					H	r
23.8 (9/8)	38.100 (1 1/2)	9.525 (3/8)	0.794 (1/16)	4.762 (3/16)	3.969 (1/8)	7.938 (3/8)	1.588 (1/16)	26.195 (1 1/8)	55.7	29 200	40 100

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060464019
Inside diameter	15.875 mm
Outside diameter	41.275 mm
Thickness	22.225 mm
Weight	265 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE