

Cam follower CR32-V-IKO - CR32-V-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr32-v-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.)					
	Shield type		Sleeved type		g	D	C	d ₁	G	G ₁
	With covered outer ring	With cylindrical outer ring	With drilled outer ring	With cylindrical outer ring				UNF		
22.225 (7/8)		CR 32 V			627	50.800 (2)	31.750 (1 1/4)	22.225 (7/8)	14	25.400 (1)

Boundary dimensions mm(inch)							Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
B max	B ₂	B ₃	C ₁	g ₁	g ₂	r				
33.5 (1.32)	50.800 (2)	12.700 (1/2)	0.794 (1/32)	4.762 (3/8)	4.762 (3/8)	1.588 (1/16)	31.268 (1 1/8)	162	45 700	80 800

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060464187
Inside diameter	22.225 mm
Inside diameter	7/8" inch
Outside diameter	50.8 mm
Outside diameter	2" inch
Thickness	31.75 mm
Thickness	1 1/4" inch
Weight	627 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE