

Cam follower CR32-VBUUR-IKO - CR32-VBUUR-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr32-vbuur-iko>

CAM FOLLOWERS

Inch Series Cam Followers **With Cage/With Screwdriver Slot**

CR32-VBUUR

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Shield type With covered outer ring	Shield type With cylindrical outer ring						
22.225 (⁷ / ₈)			CR 32	VBUUR	627	50.800 (2)	31.750 (1 ¹ / ₂)	22.225 (7 ¹ / ₈)	14	25.400 (1)

Boundary dimensions mm (inch)										Mounting dimension f Min. mm (inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
B max	B ₂	B ₃	C ₁	g ₁	g ₂	H	r						
33.5 (1 1/2)	50.800 (2)	12.700 (1/2)	0.794 (5/64)	4.762 (3/8)	4.762 (3/8)	11.112 (7/8)	1.588 (5/16)	37.305 (1 1/2)	162	45 700	80 600		

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060464231
Inside diameter	22.225 mm
Outside diameter	50.8 mm
Thickness	31.75 mm
Weight	627 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE