

Cam follower CR36-VUU-IKO - CR36-VUU-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr36-vuu-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Spigot type With offset outer ring	Spigot type With cylindrical outer ring						
22.225 ($\frac{7}{8}$)			CR 36	VUU	759	57.150 ($2\frac{1}{4}$)	31.750 ($1\frac{1}{4}$)	22.225 ($\frac{7}{8}$)	$\frac{7}{8}$ -14	25.400 (1)
Boundary dimensions mm(inch)					Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N		
B max	B ₂	B ₃	C ₁	g ₁					g ₂	r
33.5 (1.32)	33.800 (1)	12.700 ($\frac{1}{2}$)	8.794 ($\frac{3}{4}$)	4.762 ($\frac{1}{2}$)	4.762 ($\frac{1}{2}$)	1.588 ($\frac{1}{4}$)	31.268 (1.23)	162	45 700	80 800

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060464279
Inside diameter	22.225 mm
Outside diameter	57.15 mm
Thickness	31.75 mm
Weight	759 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE