


## Cam follower CR36-VUUR-IKO - CR36-VUUR-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr36-vuur-iko>

IKO

### CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inchi)	Identification number				Mass (Ref.)		D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Sealed type With shielded outer ring	Sealed type With cylindrical outer ring	g	g					
22.225 ( $\frac{7}{8}$ )			CR 36	VUUR	759	57.150 (2 $\frac{1}{2}$ )	31.750 (1 $\frac{1}{4}$ )	22.225 (7/8)	UNF-14	25.400 (1)	

Boundary dimensions mm(inch)							Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>	r				
33.5 (1.32)	33.800 (1)	12.700 ( $\frac{1}{2}$ )	5.794 ( $\frac{1}{4}$ )	4.762 ( $\frac{1}{4}$ )	4.762 ( $\frac{1}{4}$ )	1.588 ( $\frac{1}{4}$ )	31.268 (1 $\frac{1}{4}$ )	162	45 700	80 800

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060464286
Inside diameter	22.225 mm
Outside diameter	57.15 mm
Thickness	31.75 mm
Weight	759 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE