


Cam follower CR36-VBUUR-IKO - CR36-VBUUR-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr36-vbuur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Sleeve type With groove outer ring	Sleeve type With cylindrical outer ring							
22.225 ($\frac{7}{8}$)			CR 36	VBUUR	759	57.150 (2 $\frac{1}{2}$)	31.750 (1 $\frac{1}{4}$)	22.225 (7/8)	7/14	25.400 (1)	
Boundary dimensions mm (inch)						Mounting dimension f Min. mm (inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N		
B max	B ₂	B ₃	C ₁	g ₁	g ₂					H	r
33.5 (1.32)	50.800 (2)	12.700 (1/2)	0.794 ($\frac{1}{32}$)	4.762 ($\frac{3}{16}$)	4.762 ($\frac{3}{16}$)	11.112 (1/2)	1.588 ($\frac{1}{16}$)	37.305 (1 $\frac{1}{2}$)	162	45 700	80 600

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060464316
Inside diameter	22.225 mm
Outside diameter	57.15 mm
Thickness	31.75 mm
Weight	759 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE