

## Cam follower CR48-VUU-IKO - CR48-VUU-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/cr48-vuu-iko>

IKO

### CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inchi)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>	
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Spigot type With offset outer ring	Spigot type With cylindrical outer ring							
31.750 (1.25)				CR 48 VUU	1 960	76.200 (3)	44.450 (1.75)	31.750 (1.25)	1 1/4 - 12	31.750 (1.25)	
Boundary dimensions mm(inch)					Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N			
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>					g <sub>2</sub>	r	
46.4 (1.83)	83.500 (3.3)	15.875 (0.625)	1.588 (0.0625)	6.350 (0.25)	4.762 (0.1875)	2.381 (0.094)	51.981 (2.046)	500	77 600	172 000	

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952462530
Inside diameter	31.75 mm
Outside diameter	76.2 mm
Thickness	44.5 mm
Weight	1960 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE