


## Cam follower CRH12-VBUUR-IKO - CRH12-VBUUR-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/crh12-vbuur-iko>

IKO

### CAM FOLLOWERS

Inch Series Heavy Duty Cam Followers Full Complement Type/With Hexagon Hole



Stud dia. mm (inch)	Identification number		Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>	B max
	Shield type	Sealed type							
11.112 ( $\frac{7}{16}$ )	CRH 12	VBUUR	39	19.050 ( $\frac{3}{4}$ )	12.700 ( $\frac{1}{2}$ )	11.112 ( $\frac{7}{16}$ )	$\frac{7}{16}$ -20	9.525 ( $\frac{3}{8}$ )	14.6 (0.57)

Boundary dimensions mm(inch)								Mounting dimension F mm (inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N
B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	S <sub>1</sub>	S <sub>2</sub>	H	R					
22.225 ( $\frac{7}{8}$ )	6.350 ( $\frac{1}{4}$ )	6.794 ( $\frac{1}{4}$ )	4.762 ( $\frac{3}{16}$ )	2.381 ( $\frac{3}{32}$ )	4.762 ( $\frac{3}{16}$ )	250.00	13.484 ( $\frac{1}{2}$ )	17.6	8 710	12 300	

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952462943
Inside diameter	11.112 mm
Inside diameter	7/16" inch
Outside diameter	19.05 mm
Outside diameter	3/4" inch
Thickness	12.7 mm
Thickness	1/2" inch
Weight	39 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE