


Cam follower CRH36-VB-IKO - CRH36-VB-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/crh36-vb-iko>

IKO

CAM FOLLOWERS

Inch Series Heavy Duty Cam Followers Full Complement Type/With Hexagon Hole



Stud dia. mm (inch)	Identification number		Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	B max
	Shield type	Sealed type							
25.575 (1.007)	CRH 36	VB	858	57.150 (2.250)	31.750 (1.250)	28.575 (1.125)	1/4-12	25.400 (1.000)	34.2 (1.35)

Boundary dimensions mm(inch)								Mounting dimension F Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
B ₂	B ₃	C ₁	S ₁	S ₂	H	R					
50.800 (2.000)	12.700 (0.500)	1.588 (0.0625)	4.762 (0.1875)	3.175 (0.125)	11.112 (0.4375)	1.588 (0.0625)	37.306 (1.469)	356	45 700	80 800	

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060464750
Inside diameter	28.575 mm
Outside diameter	57.15 mm
Thickness	31.75 mm
Weight	858 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE