


Cam follower CRH36-VR-IKO - CRH36-VR-IKO

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/cam-follower/crh36-vr-iko>

IKO

CAM FOLLOWERS

Inch Series Heavy Duty Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inch)	Identification number		Mass (Ref.) g	D	C	d ₁	G	G ₁	B max
	Shield type	Sealed type							
28.575 (1 1/4)	CRH 36	VR	858	57.150 (2 1/2)	31.750 (1 1/2)	28.575 (1 1/4)	U ₁ -12	25.400 (1)	34.2 (1.35)

Boundary dimensions mm(inch)							Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
B ₂	B ₃	C ₁	B ₁	B ₂	R					
50.800 (2)	12.700 (1/2)	1.588 (1/8)	4.762 (3/8)	3.175 (1/4)	600 (3)	37.306 (1 1/2)	356	45 700	80 600	

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952463872
Inside diameter	28.575 mm
Outside diameter	57.15 mm
Thickness	31.75 mm
Weight	858 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE