


Roller bearing NN3024K-JTEKT - NN3024K-KOYO

<https://www.123bearing.eu/bearing-housing/roller-bearing/roller/nn3024k-koyo>

Double-row cylindrical roller bearings ————— Koyo



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min ⁻¹)		Bearing No.		
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F_w</i>	<i>E_a</i>	<i>C</i>	<i>C₀₂</i>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
120	180	46	2	—	165	232	392	3 200	3 900	—	—
				Mounting dimensions (mm)					(Refer.) Mass (kg)		
Cylindrical bore		Tapered bore		<i>d_a</i> min.	<i>d_a</i> max.	<i>d_a</i> min.	<i>d_a</i> max.	<i>D_a</i> min.	<i>r_a</i> max.	Cylindrical bore	Tapered bore
				129	—	—	171	167	2	4.00	3.87

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952473109
Inside diameter	120 mm
Outside diameter	180 mm
Thickness	46 mm
Weight	3870 g
Packaging	1
Standard	No standard

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE