


## Tapered roller bearing 45352-JTEKT - 45352-KOYO

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/45352-koyo>

Double-row tapered roller bearings  
TDI type Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	B	T	r	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.
260	440	144	144	4	1 890	3 440	560	750

Bearing No.	Mounting dimensions (mm)						Constant e	Axial load factors			(Refer.) Mass (kg)
	d <sub>1a</sub> max.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	r <sub>1a</sub> min.	r <sub>1b</sub> max.	r <sub>1c</sub> max.		Y <sub>2</sub>	Y <sub>3</sub>	Y <sub>0</sub>	
45352	313	422	386	6	3	4	0.35	1.95	2.90	1.91	92.2

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952481999
Inside diameter	260 mm
Outside diameter	440 mm
Thickness	144 mm
Weight	92200 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE