

## Roller bearing NQS55-22-JTEKT - NQS55-22-KOYO

<https://www.123bearing.eu/bearing-housing/roller-bearing/roller/nqs55-22-koyo>

Machined ring needle roller bearings Koyo

$F_w$  29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
$F_w$	d	D	B	$C_r$	$C_{10}$	Oil lub.	Without inner ring	
55	45	72	22	44.6	71.6	8 300	NQS55/22	
Mounting dimensions (mm)				[Refer.] Mass (kg)		[Refer.] Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring	—		
	$d_a$	$D_a$	$r_a$	0.210	0.341			
	max.	max.	max.					
	49	66	0.6					

[Note] 1) Limiting speeds of bearing number NA49..LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952483504
Inside diameter	55 mm
Outside diameter	72 mm
Thickness	22 mm
Weight	210 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE