

SI Rod end

DSI5-T-K-DURBAL - DSI5-T-K-DURBAL


<https://www.123bearing.eu/bearing-housing/rod-end/si/dsi5-t-k-durbal>

DSI5-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

order number

right hand thread	left hand thread
DSI 5 T/K	

measurement [mm]

d	G	B	C1	d2	d3	d4
5	M 5	8	6,00	18	8,5	11

type	measurement [mm]			d [mm]	load rating C ₀ [N]	weight [g]
	l ₃ min	W	h			
DSI / DSIK 5 T/K	10	9	27	13	6,0	0,016

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489056
Inside diameter	5 mm
Outside diameter	18 mm
Thickness	8 mm
Type	SI
Weight	16 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu
+33 359 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE