

SI Rod end SIL8-T-K-DURBAL - DSIL8-T-K-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/dsil8-t-k-durbal>


SIL8-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
	SIL 8 T/K	8	M 8	12	9,00	24	12,5	16

type	measurement [mm]			h	d ₁ PT	load rating C ₁₀ [N]	weight [kg]
	l ₁ min	W					
SI / SIL 8 T/K	16	14	36	14	12,9	0,047	

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489155
Inside diameter	8 mm
Outside diameter	24 mm
Thickness	12 mm
Type	SI
Weight	47 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE