

## SI Rod end SI12-T-K-DURBAL - SI12-T-K-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/si12-t-k-durbal>

### SI12-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE composite

**Inner ring:**  
bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:**  
brass body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:**  
maintenance free

order number	measurement (mm)
SI 12 TIK	d 12 G M 12 B 16 C1 12,00 d2 32 d3 17,5 d4 22

type	measurement (mm)			load rating	weight
	l <sub>1</sub> min	W	h	C <sub>1</sub> [kN]	[g]
SI / SI12 TIK	22	19	50	24,0	0,100

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489285
Inside diameter	12 mm
Outside diameter	32 mm
Thickness	16 mm
Type	-
Weight	100 g
Thread	-
Lubrication	-
Packaging	-

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE