

SI Rod end SI30-T-K-DURBAL - SI30-T-K-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/si30-t-k-durbal>


SI30-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

| order number | measurement (mm) |
|--------------|---|
| SI 30 TIK | d 30 G M 30 x 2 B 37 C1 25,00 d2 70 d3 40,0 d4 50 |

| type | measurement (mm) | | | load rating C ₅ [kN] | weight [kg] |
|-----------------|--------------------|----|-----|---------------------------------------|----------------|
| | l ₃ min | W | h | | |
| SI / SIL 30 TIK | 51 | 41 | 110 | 17 | 114,0 |

PRODUCT FEATURES

| | |
|------------------|-------------------|
| Brand | DURBAL |
| N° Ean13 | 3663952489698 |
| Inside diameter | 30 mm |
| Outside diameter | 70 mm |
| Thickness | 37 mm |
| Type | SI |
| Weight | 1100 g |
| Thread | Right-hand thread |
| Lubrication | without |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE