

SI Rod end

SIL30-T-K-DURBAL - SIL30-T-K-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/sil30-t-k-durbal>


SIL30-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

| order number | right hand thread | left hand thread | d | G | B | C ₁ | d ₂ | d ₃ | d ₄ |
|--------------|-------------------|------------------|----|----------|----|----------------|----------------|----------------|----------------|
| SIL 30 T/K | | | 30 | M 30 x 2 | 37 | 25,00 | 70 | 40,0 | 50 |

| type | measurement (mm) | | | d ₁ | load rating C ₁₀ (N) | weight (kg) |
|-----------------|--------------------|----|-----|----------------|---------------------------------|-------------|
| | l ₁ min | W | h | | | |
| SI / SIL 30 T/K | 51 | 41 | 110 | 17 | 114,0 | 1,100 |

PRODUCT FEATURES

| | |
|------------------|------------------|
| Brand | DURBAL |
| N° Ean13 | 3663952489728 |
| Inside diameter | 30 mm |
| Outside diameter | 70 mm |
| Thickness | 37 mm |
| Type | SI |
| Weight | 1100 g |
| Thread | Left-hand thread |
| Lubrication | without |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE