

# SI Rod end SI30M27X2-T-K-DURBAL - SI30M27X2-T-K-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/si30m27x2-t-k-durbal>

## SI30M27X2-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE composite

**Inner ring:**  
bearing steel, hardened, ground and  
spherical surface chromium plated

**Outer ring:**  
brass body pressed around, outer race  
lined with bronze-PTFE composite

**Lubrication:**  
maintenance free

order number	right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
SI 30 TIK M 27 x 2			30	M 27 x 2	37	25,00	70	40,0	50

type	measurement (mm)			h	d <sub>1</sub> PT	load rating C <sub>10</sub> (N)	weight (kg)
	l <sub>3</sub> min	W					
SI / SIL 30 TIK M 27 x 2	51	41		110	17	114,0	1,100

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489766
Inside diameter	30 mm
Outside diameter	70 mm
Thickness	37 mm
Type	SI
Weight	1100 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE