

SI Rod end

SIL40-T-K-DURBAL - SIL40-T-K-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/sil40-t-k-durbal>


SIL40-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	measurement [mm]
right hand thread left hand thread SIL 40 T/K	d G B C ₁ d ₂ d ₃ d ₄
	40 M 42 x 2 49 33,00 91 53,0 65

type	measurement [mm]			load rating C ₅ [kN]	weight [kg]
	l ₁ min	W	h		
SI / SIL 40 T/K	60	55	142	17	2,400

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489810
Inside diameter	40 mm
Outside diameter	91 mm
Thickness	49 mm
Type	SI
Weight	2400 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE