


SA Rod end
DSAL6-T-K-DURBAL - DSAL6-T-K-DURBAL
<https://www.123bearing.eu/bearing-housing/rod-end/sa/dsal6-t-k-durbal>


DSAL6-T-K



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C ₁	d ₂	
DSAL 6 T/K		6	M 6	9	6,75	20	

type	measurement [mm]		h	α [°]	Tragzahlen C ₁₀ [kN]	weight [kg]
	l ₁ min	l ₂				
DSA / DSAL 6 T/K	21		36	13	7,7	0,020

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489940
Inside diameter	6 mm
Outside diameter	20 mm
Thickness	9 mm
Type	SA
Weight	20 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE