

**SA Rod end**  
**SA25-T-K-DURBAL - SA25-T-K-DURBAL**  
<https://www.123bearing.eu/bearing-housing/rod-end/sa/sa25-t-k-durbal>


**SA25-T-K**



male thread;  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE composite

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
brass body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
maintenance free

order number	measurement [mm]		C <sub>1</sub>	d <sub>2</sub>
	d	G		
SA 25 T/K	25	M 24 x 2	31	22,00

type	measurement [mm]		h	α [°]	Tragzahlen C <sub>10</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub>				
SA / SAL 25 T/K	55	30	94	15	85,0	0,640

**PRODUCT FEATURES**

Brand	DURBAL
N° Ean13	3663952490298
Inside diameter	25 mm
Outside diameter	60 mm
Thickness	31 mm
Type	SA
Weight	640 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE