

**SA Rod end**  
**SAL40-T-K-DURBAL - SAL40-T-K-DURBAL**  
<https://www.123bearing.eu/bearing-housing/rod-end/sa/sal40-t-k-durbal>

**SAL40-T-K**



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

**male thread:** maintenance free, according to DIN ISO 12240-4, series K

**Rod end body:** surface zinc plated

**Sliding combination:** steel / bronze-PTFE composite

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** brass body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
SAL 40 T/K		40	M 42 x 2	49	33,00	91

  

type	measurement [mm]		h	α [°]	Tragzahlen C <sub>10</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub>				
SA / SAL 40 T/K	90	46	150	17		2,300

**PRODUCT FEATURES**

Brand	DURBAL
N° Ean13	3663952490489
Inside diameter	40 mm
Outside diameter	91 mm
Thickness	49 mm
Type	SA
Weight	2300 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)  
+33 359 36 04 90  
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE