

SA Rod end SSA6-T-K-DURBAL - SSA6-T-K-DURBAL

https://www.123bearing.eu/bearing-housing/rod-end/sa/ssa6-t-k-durbal

SSA6-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]			
SSA 6 T/K	6	M 6	G	B	C1	d2
			6	9	6,75	20

type	measurement [mm]		h	alpha [°]	load rating C0 [kN]	weight [kg]
	l1 min	l2 min				
SSA / SSAL 6 T/K	21	36	13	7,7	0,020	

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490595
Inside diameter	6 mm
Inside diameter	0.236" inch
Outside diameter	20 mm
Outside diameter	0.787" inch
Thickness	9 mm
Thickness	0.354" inch
Type	SA
Weight	20 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE