

SA Rod end SSAL14-T-K-DURBAL - SSAL14-T-K-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/ssal14-t-k-durbal>

SSAL14-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	d	G	measurement [mm]	B	C1	d2
SSAL 14 T/K	14	M 14		19	13,50	36

type	measurement [mm]			alpha [°]	load rating C0 [kN]	weight [kg]
	l1 min	l2 min	h			
SSA / SSAL 14 T/K	36	18	60	16	31,0	0,140

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490748
Inside diameter	14 mm
Outside diameter	36 mm
Thickness	19 mm
Type	SA
Weight	140 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE