

# SA Rod end SSA16-T-K-DURBAL - SSA16-T-K-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/ssa16-t-k-durbal>

## SSA16-T-K



**male thread:** maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

**rod end body:** stainless steel

**Sliding combination:** steel / bronze-PTFE composite

**inner ring:** stainless steel, hardened and ground

**Outer ring:** stainless steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

order number	right hand thread	left hand thread	measurement [mm]			
SSA 16 T/K	16		M 16	21	15,00	42

type	measurement [mm]			alpha [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub> min	h			
SSA / SSA 16 T/K	37	21	66	15	39,0	0,210

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490786
Inside diameter	16 mm
Outside diameter	42 mm
Thickness	21 mm
Type	SA
Weight	210 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE