

SI Rod end DSSI5-T-K-DURBAL - SSI5-T-K-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/ssi5-t-k-durbal>

DSSI5-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
			d	G	B	C ₁	d ₁	d ₂	d ₃	d ₄
DSSI 5 T/K			5	M 5	8	6,00	18	8,5	11	

type	measurement [mm]				α °FS	load rating C ₀ [kN]	weight [g]
	l ₁ min	W	h				
DSSI / DSSIL 5 T/K	10	9	27	13	6,0	0,016	

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952491059
Inside diameter	5 mm
Outside diameter	18 mm
Thickness	8 mm
Type	SI
Weight	16 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE