

## SI Rod end DSSIL5-T-K-DURBAL - DSSIL5-T-K-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/dssil5-t-k-durbal>

### DSSIL5-T-K



**female thread:** maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

**Red end body:** stainless steel

**Sliding combination:** steel / bronze-PTFE composite

**Inner ring:** stainless steel, hardened and ground

**Outer ring:** stainless steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
DSSIL 5 T/K			d	G	B	C1	d1	d2	d3	d4
			5	M 5	8	6,00	18	8,5	11	

type	measurement [mm]				load rating C <sub>0</sub> [kN]	weight [g]
	l <sub>1</sub> min	W	h	α [°]		
DSSIL / DSSIL 5 T/K	10	9	27	13	6,0	0,016

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952491080
Inside diameter	5 mm
Outside diameter	18 mm
Thickness	8 mm
Type	SI
Weight	16 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE