

SI Rod end DSSIL8-T-K-DURBAL - DSSIL8-T-K-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/dssil8-t-k-durbal>

DSSIL8-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
DSSIL 8 T/K			d	G	B	C1	d1	d2	d3	d4
			8	M 8	12	9,00	24	12,5	16	

type	measurement [mm]			load rating	weight
	l1 min	W	h	C0 (kN)	Bgl
DSSIL / DSSIL 8 T/K	16	14	36	12,5	0,047

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952491165
Inside diameter	8 mm
Outside diameter	24 mm
Thickness	12 mm
Type	SI
Weight	47 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE