

## SI Rod end DSSIL12-T-K-DURBAL - DSSIL12-T-K-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/dssil12-t-k-durbal>

### DSSIL12-T-K



**female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel**

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

**Rod end body: stainless steel**

**Sliding combination:** steel / bronze-PTFE composite

**Inner ring:** stainless steel, hardened and ground

**Outer ring:** stainless steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

| order number | right hand thread | left hand thread | measurement [mm] |      |    |       |    |      |    |    |
|--------------|-------------------|------------------|------------------|------|----|-------|----|------|----|----|
| DSSIL 12 T/K |                   |                  | d                | G    | B  | C1    | d1 | d2   | d3 | d4 |
|              |                   |                  | 12               | M 12 | 16 | 12,00 | 32 | 17,5 | 22 |    |

| type                | measurement [mm]   |    |    |          | load rating<br>C <sub>0</sub><br>[kN] | weight<br>[kg] |
|---------------------|--------------------|----|----|----------|---------------------------------------|----------------|
|                     | l <sub>1</sub> min | W  | h  | α<br>[°] |                                       |                |
| DSSI / DSSIL 12 T/K | 22                 | 19 | 50 | 13       | 24,0                                  | 0,100          |

## PRODUCT FEATURES

|                  |                  |
|------------------|------------------|
| Brand            | DURBAL           |
| N° Ean13         | 3663952491264    |
| Inside diameter  | 12 mm            |
| Outside diameter | 32 mm            |
| Thickness        | 16 mm            |
| Type             | SI               |
| Weight           | 100 g            |
| Thread           | Left-hand thread |
| Lubrication      | without          |
| Packaging        | 1                |

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE