

SI Rod end SSI25-T-K-DURBAL - DSSI25-T-K-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/dssi25-t-k-durbal>

SSI25-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
SSI 25 T/K			d	G	B	C ₁	d ₁	d ₂	d ₃	d ₄
			25	M 24 x 2	31	22,00	60	33,5	42	

type	measurement [mm]				α °	load rating C ₀ [kN]	weight [kg]
	l ₁ min	W	h	α			
SSI / SSI 25 T/K	42	36	94	15	85,0	0,720	

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952491615
Inside diameter	25 mm
Outside diameter	60 mm
Thickness	31 mm
Type	SI
Weight	720 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE