

# SI Rod end SSI28-T-K-DURBAL - DSSI28-T-K-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/dssi28-t-k-durbal>

## SSI28-T-K



**female thread:** maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

**Rod end body:** stainless steel

**Sliding combination:** steel / bronze-PTFE composite

**Inner ring:** stainless steel, hardened and ground

**Outer ring:** stainless steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
			d	G	B	C <sub>1</sub>	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
SSI 28 T/K			28	M 27 x 2	35	24,00	66	37,0	46	

type	measurement [mm]				α °FS	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	W	h				
SSI / SSI 28 T/K	51	41	103	15	107,0	0,820	

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952491684
Inside diameter	28 mm
Outside diameter	66 mm
Thickness	35 mm
Type	SI
Weight	820 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE