

## SI Rod end DSIL14-PK-DURBAL - DSIL14-PK-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/dsil14-pk-durbal>

### DSIL14-PK



**female thread; maintenance free, according to DIN ISO 12240-4, series K**

**Description:** DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

**End end body:** surface case plated

**Sliding combination:** steel / bronze-PTFE composite

**Inner ring:** bearing steel hardened and ground

**Outer ring:** rod end body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

order number	d	G	measurement (mm)				
right hand thread	B	C1	d1	d2	d3	d4	
<b>DSIL 14 PK</b>	14	M 14	19	14,00	37	20,0	25

type	measurement (mm)			alpha	load rating	weight
	ly min	W	h	[°]	C0 (kN)	(kg)
<b>DSI / DSIL 14 PK</b>	25	22	57	14	31,00	0,160

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492056
Inside diameter	14 mm
Inside diameter	0.551" inch
Outside diameter	37 mm
Outside diameter	1.457" inch
Thickness	19 mm
Thickness	0.748" inch
Type	SI
Weight	160 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE