

SI Rod end

DSIL20-PK-DURBAL - DSIL20-PK-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/dsil20-pk-durbal>

DSIL20-PK



female thread; maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

rod end body: surface case plated

Sliding combination: steel / bronze-PTFE composite

inner ring: bearing steel hardened and ground

Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

| order number | measurement (mm) | | | | | |
|-------------------|------------------|------------|----|-------|----|------|
| right hand thread | d | G | B | C1 | d2 | d4 |
| DSIL 20 PK | 20 | M 20 x 1,5 | 25 | 18,00 | 51 | 27,5 |

| type | measurement (mm) | | | | load rating | weight |
|-------------------------|------------------|----|----|-----------|-------------|--------|
| | ly min | w | h | alpha [°] | C0 (kN) | (kg) |
| DSI / DSIL 20 PK | 33 | 30 | 77 | 14 | 57,00 | 0,420 |

PRODUCT FEATURES

| | |
|------------------|------------------|
| Brand | DURBAL |
| N° Ean13 | 3663952492216 |
| Inside diameter | 20 mm |
| Outside diameter | 51 mm |
| Thickness | 25 mm |
| Type | SI |
| Weight | 420 g |
| Thread | Left-hand thread |
| Lubrication | without |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE