

SI Rod end DSIL25-PK-DURBAL - DSIL25-PK-DURBAL

https://www.123bearing.eu/bearing-housing/rod-end/si/dsil25-pk-durbal

DSIL25-PK



female thread; maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

rod end body: surface case plated

Sliding combination: steel / bronze-PTFE composite

inner ring: bearing steel hardened and ground

Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	measurement (mm)					
right hand thread	d	G	B	C1	d2	d3
DSIL 25 PK	25	M 24 x 2	31	22,00	61	33,5

type	measurement (mm)			load rating	weight
	ly min	w	h	C0 (N)	(kg)
DSI / DSIL 25 PK	42	36	94	85,00	0,720

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492292
Inside diameter	25 mm
Outside diameter	61 mm
Thickness	31 mm
Type	SI
Weight	720 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE