

SA Rod end DSA8-BK-DURBAL - DSA8-BK-DURBAL


<https://www.123bearing.eu/bearing-housing/rod-end/sa/dsa8-bk-durbal>

DSA8-BK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel hardened and ground

Outer ring:
rod end body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	measurement [mm]		measurement [mm]		
	d	G	B	C ₁	d ₂
DSA 8 BK	8	M 8	12	9,0	25

type	measurement [mm]		load rating C ₀ [kN]	weight [kg]
	l ₁ min	h		
DSA / DSAL 8 BK	25	42	12,90	0,038

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492407
Inside diameter	8 mm
Inside diameter	0.315" inch
Outside diameter	25 mm
Outside diameter	0.984" inch
Thickness	12 mm
Thickness	0.472" inch
Type	SA
Weight	38 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE