

SA Rod end SAL10-BK-DURBAL - SAL10-BK-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/sal10-bk-durbal>

SAL10-BK



male thread: maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel hardened and ground

Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	measurement [mm]	
	right hand thread	left hand thread
SAL 10 BK	10	M 10

type	measurement [mm]		alpha [°]	load rating C ₀ [kN]	weight [g]
	l ₁ min	h			
SA / SAL 10 BK	29	48	12	18,00	0,055

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492452
Inside diameter	10 mm
Outside diameter	29 mm
Thickness	14 mm
Type	SA
Weight	55 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE