

## SA Rod end DSA16-BK-DURBAL - DSA16-BK-DURBAL


<https://www.123bearing.eu/bearing-housing/rod-end/sa/dsa16-bk-durbal>

### DSA16-BK



male thread;  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



Rod end body:

surface zinc plated

Sliding combination:

steel / bronze-PTFE composite

Inner ring:

bearing steel hardened and ground

Outer ring:

rod end pressed around, outer race lined with bronze-PTFE composite

Lubrication:

maintenance free

order number	measurement [mm]		measurement [mm]		
	d	G	B	C <sub>1</sub>	d <sub>2</sub>
DSA 16 BK	16	M 16	21	15,0	43

type	measurement [mm]		alpha [°]	load rating C <sub>0</sub> [kN]	weight [g]
	l <sub>1</sub> min	h			
DSA / DSAL 16 BK	40	66	14	39,00	0,210

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492568
Inside diameter	16 mm
Outside diameter	43 mm
Thickness	21 mm
Type	SA
Weight	210 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE