

SA Rod end SA20-BK-DURBAL - SA20-BK-DURBAL


<https://www.123bearing.eu/bearing-housing/rod-end/sa/sa20-bk-durbal>

SA20-BK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



rod end body:
surface zinc plated
Sliding combination:
steel / bronze-PTFE composite
inner ring:
bearing steel hardened and ground
Outer ring:
rod end body pressed around, outer race
lined with bronze-PTFE composite
Lubrication:
maintenance free

order number	measurement [mm]		measurement [mm]				
	right hand thread	left hand thread	d	G	B	C ₁	d ₂
SA 20 BK			20	M 20 x 1,5	25	18,0	51

type	measurement [mm]		alpha [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	h			
SA / SA 20 BK	47	78	14	57,00	0,380

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492650
Inside diameter	20 mm
Outside diameter	51 mm
Thickness	25 mm
Type	SA
Weight	380 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE