

## SA Rod end SAL22-BK-DURBAL - DSAL22-BK-DURBAL


<https://www.123bearing.eu/bearing-housing/rod-end/sa/dsal22-bk-durbal>

### SAL22-BK



male thread;  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



rod end body:  
surface zinc plated  
Sliding combination:  
steel / bronze-PTFE composite  
inner ring:  
bearing steel hardened and ground  
Outer ring:  
rod end pressed around, outer race  
lined with bronze-PTFE composite  
Lubrication:  
maintenance free

order number	measurement [mm]		C <sub>1</sub>	d <sub>2</sub>
	d	G		
SAL 22 BK	22	M 22 x 1,5	28	55

type	measurement [mm]		α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	h			
SA / SAL 22 BK	50	84	15	68,00	0,480

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492698
Inside diameter	22 mm
Outside diameter	55 mm
Thickness	28 mm
Type	SA
Weight	480 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE