

## SA Rod end SA25-BK-DURBAL - DSA25-BK-DURBAL


<https://www.123bearing.eu/bearing-housing/rod-end/sa/dsa25-bk-durbal>

### SA25-BK



male thread;  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



rod end body:  
surface zinc plated  
Sliding combination:  
steel / bronze-PTFE composite  
inner ring:  
bearing steel hardened and ground  
Outer ring:  
rod end body pressed around, outer race  
lined with bronze-PTFE composite  
Lubrication:  
maintenance free

order number	measurement [mm]		measurement [mm]				
	right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
SA 25 BK			25	M 24 x 2	31	22,0	61

type	measurement [mm]		α [°]	load rating C <sub>0</sub> [kN]	weight [g]
	l <sub>1</sub> min	h			
SA / SAL 25 BK	57	94	15	85,00	0,640

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492735
Inside diameter	25 mm
Outside diameter	61 mm
Thickness	31 mm
Type	SA
Weight	640 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE