

SA Rod end SAL25-BK-DURBAL - SAL25-BK-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/sal25-bk-durbal>

SAL25-BK



male thread: maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel hardened and ground

Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]	
right hand thread	left hand thread	d	G
SAL 25 BK		25	M 24 x 2
			B
			31
			C1
			22,0
			d2
			61

type	measurement [mm]		alpha [°]	load rating C0 [kN]	weight [kg]
	l1 min	h			
SA / SAL 25 BK	57	94	15	85,00	0,640

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492742
Inside diameter	25 mm
Outside diameter	61 mm
Thickness	31 mm
Type	SA
Weight	640 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE