

SA Rod end GAL12-UK-DURBAL - GAL12-UK-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/gal12-uk-durbal>


GAL12-UK



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	d	G	measurement (mm)		
right hand thread	left hand thread		B	C ₁	d ₂
GAL 12 UK	12	M 12	10	8,0	34

type	measurement [mm]		h	α [°]	load rating C ₀ [kN]	weight [kg]
	l, min	l ₁ min				
GAR / GAL 12 UK	28	18	54	11	24,5	0,086

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492896
Inside diameter	12 mm
Outside diameter	34 mm
Thickness	10 mm
Type	SA
Weight	86 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE