

SA Rod end GAR20-UK-DURBAL - GAR20-UK-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/gar20-uk-durbal>

GAR20-UK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	d	G	B	C1	d2
right-hand thread					
left-hand thread					
GAR 20 UK	20	M 20 x 1,5	16	13,0	53

type	measurement [mm]		h	alpha [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂ min				
GAR / GAL 20 UK	43	27	78	9	60,0	0,310

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493053
Inside diameter	20 mm
Outside diameter	53 mm
Thickness	16 mm
Type	SA
Weight	310 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE