

SA Rod end GAR25-UK-2RS-DURBAL - GAR25-UK-2RS-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/gar25-uk-2rs-durbal>


GAR25-UK-2RS



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	measurement (mm)	
right hand thread	d	G
left hand thread	B	C ₁
GAR 25 UK (-2RS)	25	M 24 x 2
	20	17,0
	64	

type	l, min	measurement [mm]	h	α [°]	load rating C ₀ [kN]	weight [kg]
GAR / GAL 25 UK-2RS	53	32	94	7	83,0	0,560

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493176
Inside diameter	25 mm
Inside diameter	0.984" inch
Outside diameter	64 mm
Outside diameter	2.52" inch
Thickness	20 mm
Thickness	0.787" inch
Type	SA
Weight	560 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE